

Trittico[®] Executive 457

Combined machine with ionic-system and double inverter for pastry products, chocolate, savoury food and gelato

water cooled















Absolute Creative Freedom

Trittico® Executive is the first and only complete laboratory enclosed in just one machine: more than 40 years of innovation in less than 10 square feet. Trittico® Executive harbors the unique synergy of ancient experience, craftsmanship, and avantgarde technology in its very heart. For the art of pastry making, chocolate, top quality gelato, and for the highest levels of international cousine.

Technical features

- · Ingredients can be added during each heating or freezing phase
- Double inverter for upper tank stirrer with 3 speeds and batch-freezer mixer with 8 speeds
- · Sheet resistance heating system: very quick heating process, no thermal hysteresis, high temperature precision, product never burns
- Patented ionic® System control: it detects the right percentage of frozen water in the mixture in order to obtain the proper gelato/ sorbet consistency and volume
- Thermal shock due to fast temperature decrease from 85°C to 4°C: it allows the highest sanitizing of the product and the highest hygiene of the mixture
- · Software programmed with multiple recipes
- · Special whisk to whip
- · Chute for direct extraction

Advantages and strengths

- · Very easy and convenient product loading
- · Mixing speed can be changed either automatically or manually
- · Fast washing operations
- · Max hygene
- · Extremely easy to handle and clean



Trittico Executive 457

Combined machine with ionic-system and double inverter for pastry products, chocolate, savoury food and gelato

water cooled

| Model: |
|------------|
| Quantity: |
| Project: |
| Company: |
| Contact: |
| Dealer ID: |

| Rece for electrical wiring Electrical wires inside tubing or raceway Differential switch (****) Disconnecting switch to CE norms Dinking water delivery tube 0 1/2' Water discharge tube 0 3/4' Ball cock 0 1/2' Ball cock 0 1/2' Sovered rubber hose inside 0 13 for pressure up to 1000 kPa (10 bar) UNCIG 7140 Water drainage raceway for grating's ground side view front view | C | | A |
|---|---|--|--|
| | 3.937 (** Water drainage raceway for grating's ground | Drinking water delivery tube Ø 1/2 Drinking water delivery tube Ø 1/2 Water discharge tube Ø 3/4 Ball cock Ø 1/2 Covered rubber hos inside Ø 13 for pressure up to 1000 kPa (10 bar) UNICIG 7140 | Electrical wires inside iubing or raceway Differential switch (***) Disconnecting switch to (E norms (*) 17.717 IN (*) 1.949 IN Filling Discharge Filter upstream of system |
| | 5.45 | | , |





Warranty: valid for the North American Continent (Canada, USA)
Extension: 12 months parts (with check list and warranty signed and mailed)
5 years compressor with registration on warranty.bravonorthamerica.com

| Width (A) | cm | 51 | inches | 20,1 |
|---|--|------------|----------|--------------|
| Depth (B) | cm | 95 | inches | 37,4 |
| Depth with base (C) | cm | 102,5 | inches | 40,4 |
| Height (H) | cm | 140 | inches | 55,1 |
| Weight | kg | 309 | lbs | 681 |
| Frame type | floor model | | | |
| Outer panels | | stainle | ss steel | |
| Capacity per cycle | Liters | 7 | Gal | 1,84 |
| Max. hourly production for gelato | Liters | 45 | Gal | 11,88 |
| Max. hourly production for pastry | based on the product that has to be produced | | | |
| Min. mix per cyle | Kg | 2,5 | Lbs | 5,5 |
| Max. mix per cyle | Kg | 5,5 | Lbs | 12,1 |
| Volume cylinder with mixer | Liters | 11,78 | Quarts | 12,45 |
| Volume cylinder without mixer | Liters | 12,42 | Quarts | 13,12 |
| Stirrer speed | 3 speeds from 30 to 80 RPM | | | |
| Mixer speed | 8 speeds from 20 to 300 RPM | | | |
| Max power | kw | 6,3 | Нр | 8,4 |
| Voltage | 230 Volt / 60 Hz / 3 phase | | | |
| Running Amps | Amp 21 | | | |
| Breaker size | Amp 30 | | | |
| Stirrer motor | kw | 0,22 | Нр | 0,3 |
| Drive motor | kw | 3,3 - 2,2 | Нр | 4,5 - 3 |
| Compressor power | kw | 2,8 | Нр | 3,75 |
| Compressor power | BTU/h 9349 | | | |
| Freon R404A | Gr | 1200 | Oz | 42 |
| Refrigeration condensation | Water | | | |
| Water connection | cm | 1,27 | inches | 1/2 |
| Min. water pressure | bar | 1,5 | psi | 20 |
| Max. water pressure | bar | 3 | psi | 40 |
| Crate dimensions | cm | 110x80x172 | inches | 42,9x29x67,7 |
| Crate weight | kg | 380 | lbs | 850 |