

Gelmatic 30 M

batch-freezer for gelato & ice cream production with cold process

air cooled









Easy & fast

High performance batch-freezer that allows to obtain results above market standards. Easy to use, strong and reliable, it makes artisan's work easy and safe, as it reaches very low temperature in a very short time.

Technical features

- · Dual Mode System, for gelato and premium Ice-cream production
- · Charging hopper allows for a fast charge of the mix, flavors and other ingredients
- · Front door made in Makrolon® (special thermal insulating material)
- · Quick and easy gelato extraction
- · Acoustic signal tells you when gelato is ready
- · Automatic temperature control thanks to advanced thermoregulators with "sensible touch" displays
- · Dedicated program for premium ice cream production
- · Cylinder type: patented stainless steel "multi-point" injection system
- · Refrigeration system: patented stainless steel plate condenser
- · Three blade stainless steel mixer with interchangeable scrapers
- · Two-speed mixer
- · Probe in direct contact with the mix

Advantages and strengths


- · Gelato or ice cream batches produced in a very short time
- · Easy to use, the machine is exceptionally functional
- · Electronic control of working cycle through temperatures
- · Extremely easy to handle and clean
- · Short freezing time



Gelmatic 30 M

batch-freezer for gelato & ice cream production with cold process

air cooled



| В | Α |
|---|---|
| В п п п п п п п п п п п п п п п п п п п | 000 0000 |
| | |
| | |
| · | U U |
| Water drainage raceway for grating's ground | Electrical wiring Electrical wires inside fubing or raceway Differential switch (***) Disconnecting switch to CE norms |
| side view | front view |

| | pı |
|--------|----|
| | М |
| | Μ |
| | W |
| e - | V |
| **) | М |
| 1 | Μ |
| | М |
| | ٧ |
| | R |
| | В |
| | D |
| | С |
| | С |
| | Fi |
| | R |
| | C |

(***) 30 mA (ABB serie C).

| c Uster US | | | | |
|------------|--|--|--|--|
| Intertek | | | | |



Warranty: valid for the North American Continent (Canada, USA) Extension: 12 months parts (with check list and warranty signed and mailed) 5 years compressor with registration on warranty.bravonorthamerica.com

| Width (A) | cm | 51 | inches | 20,1 | | |
|-------------------------------|----------------------------|------------|--------|----------------|--|--|
| Depth (B) | cm | 97 | inches | 38,2 | | |
| Depth with base (C) | cm | 103,5 | inches | 40,7 | | |
| Height (H) | cm | 140 | inches | 55,1 | | |
| Weight | kg | 240 | lbs | 529 | | |
| Frame type | floor model | | | | | |
| Outer panels | stainless steel | | | | | |
| Capacity per cycle | Liters | 5 | Gal | 1,32 | | |
| Max. hourly production | Liters | 38 | Gal | 10 | | |
| Min. mix per cyle | Kg | 2 | Lbs | 4,4 | | |
| Max. mix per cyle | Kg | 4 | Lbs | 8,8 | | |
| Volume cylinder with mixer | Liters | 8,93 | Quarts | 9,43 | | |
| Volume cylinder without mixer | Liters | 9,46 | Quarts | 10 | | |
| Min. mixer speed | RPM 122 | | | | | |
| Max. mixer speed | RPM 250 | | | | | |
| Max power | kw | 2,8 | Нр | 3,7 | | |
| Voltage | 230 Volt / 60 Hz / 3 phase | | | | | |
| Running Amps | Amp 12,5 | | | | | |
| Breaker size | Amp 25 | | | | | |
| Drive motor | kw | 2,2 - 1,5 | Нр | 3-2 | | |
| Compressor power | kw | 1,3 | Нр | 1,75 | | |
| Compressor power | BTU/h 4094 | | | | | |
| Freon R404A | Gr | 2100 | Oz | 74,1 | | |
| Refrigeration condensation | Air | | | | | |
| Crate dimensions | cm | 109x69x172 | inches | 42,9x27,1x67,7 | | |
| Crate weight | kg | 330 | lbs | 727 | | |